

*Cushion*  
**MATS**

**PLAIN & DESIGN  
CARPETS**



**WOODEN / VINYL  
FLOORING**

**VENETIAN & VERTICAL  
BLIND**



**WALL PAPER  
&  
FILM**



**A. K. INTERNATIONAL**

12/1, S. A. ALI AVE., KOL. - 17, PHONE : 2281-7518, 2280-9034/ 9830117275



END00009802



END00009803



END00009804



END00009805



END00009815

# Marvel

Impacting Your Life Since 1985

**Product Range :**

- PVC Floor Coverings • PVC Synthetic Leather
- PVC Films and Sheetings • Technical Coated Textiles
- Specialty Coatings



END00009806



END00009814



END00009807



END00009811




END00009810



END00009809



END00009808

















# Marvel

## ENDURA FLOOR

Marvel's ENDURA FLOOR is a heavy-duty flooring used for applications that require good traction and durability. Endura floor is a homogeneous multi layered vinyl product, which is abrasive & wear-resistant. It can be designed and modified to fit special customer requirements. Anti Skid in nature, it is used for extra heavy-duty traffic applications and is offered in various colors and thicknesses, while being highly customizable in terms of physical properties. Endura Floor can be manufactured to have anti-bacterial, fungus resistance or any other property based on the end application. Earthy shades and modest textures harmonize almost any design scheme you can think of, from the cool and contemporary to the warm and classic. Endura Floor is best suited for offices, commercial areas, warehouses, factories, exhibition centers, porta cabins, etc. The packing offered is in rolls and tiles of various sizes and the material can be offered in a marbled finish.

### PERFORMANCE CHARACTERISTICS

 <b>THICKNESS mm</b> EN 428 2.00 mm  Other Thicknesses available from 1.0mm-3.0mm	 <b>SLIP RESISTANCE</b> DIN 51130	 <b>SHEET</b> EN 426 2.0mm X 2mtr. X 15 mtr. = 30sq. mtr.  or as per buyer specification Tile Size 305mm X 305mm, 610mm X 610mm
 <b>DIMENSIONAL STABILITY</b> EN 434 <0.40% (CK Quality)	 <b>RESIDUAL INDENTATION</b> EN 433 <0.10 mm	 <b>CASTOR CHAIR</b> EN 425 Suitable
 <b>WEIGHT</b> EN 430 3.6 Kg/Sq. mtr. for 2.0 mm	 <b>ABRASION RESISTANCE</b> (cc) ISO:9352 0.35 cc (max.)	 <b>FUNGI &amp; BACTERIA RESISTANCE</b> Does not favor growth
 <b>PLY ADHESION (KN/M)</b> IS: 3464:86 1.05 (min.)	 <b>LIGHT FASTNESS</b> ISO 105-B02] > Blue wool standard 6	 <b>WIDTH (MTRS.)</b> IS:3464:86 2.0 +/- 0.10
 <b>THICKNESS OF WEAR LAYER (MM)</b> EN 429 0.25	 <b>FLEXIBILITY AT LOW TEMPERATURE</b> IS:3462:86 Shall not break, crack or show any other sign of failure	

### RECOMMENDATIONS

**Adhesives**

We recommend Dunlop S-70 / Fovizol St. 996 or any equivalent rubber based adhesive for laying.

**Installation**

Ensure subfloor is smooth, clean, dry and structurally sound.

**Application**

ENDURA FLOOR is recommended for heavy/medium traffic areas where an attractive, modern and hard wearing floor covering at low maintenance cost is required. Most suitable for Industries, Airports, Public Offices, Banks, Hospitals, Auditoriums, Schools etc. Ideal for maintaining "clean room" condition. ENDURA FLOOR can also be thermowelded.

**Maintenance**

Occasional use of a pole mounted deck brush or a brush attachment on a low speed scrubbing machine and neutral pH cleaning solution will loosen ingrained dirt. This can then easily be removed by rinsing or mopping with a wet cloth.

**Chemical Resistance**

ENDURA FLOOR products are normally resistant to mild diluted acids & alkalis. The surface must be cleaned immediately if concentrated acids or alkalis spill.