



Cushion
MATS

**PLAIN & DESIGN
CARPETS**



**WOODEN / VINYL
FLOORING**

**VENETIAN & VERTICAL
BLIND**



**WALL PAPER
&
FILM**



A. K. INTERNATIONAL

12/1, S. A. ALI AVE., KOL. - 17, PHONE : 2281-7518, 2280-9034/ 9830117275

Homogeneous Vinyl Flooring
Talitha® Classic



4349-381-4



4349-382-4

Available in 1.00 mm.




4349-383-4



4349-384-4



4349-385-4



4349-386-4



4349-387-4



4349-388-4



4349-389-4

























4349-390-4



4349-391-4

RESPONSIVE Vinyl Flooring

The solution to every flooring need

Talitha® Classic	Technical Data		Talitha® Classic
<ul style="list-style-type: none"> Laminated Homogeneous Vinyl Flooring Polyurethane Reinforced 	 EN 685 : 1996 EN 649 : 1997 GENERAL PERFORMANCE: / TYPE OF FLOOR COVERING:		<ul style="list-style-type: none"> Homogeneous Vinyl Flooring Polyurethane Reinforced
1.50 mm 2.00 mm	IS: 3462/06	 THICKNESS:	EN 428 1.00 mm
1.5mm: 2m x 15m = 30m ² 2.0mm: 2m x 15m = 30m ²	IS: 3462/06	 SHEET:	EN 426 1.0mm: 2m x 20m = 40m ²
30 x 30 cm 100 Tiles / box - 9 m ²	IS: 3462/06	 TILES:	EN 427 610mm x 610mm
		 WEIGHT:	EN 430 1.0mm: 4.70 kg/m ² (Max.)
Does not support combustion	IS: 3464/06	 REACTION TO FIRE: / FIRE RESISTANCE:	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E848-06 Class Bfl-S1 ≥ 8 kw/m ² Pass Type I
< 40 mm	IS: 3462/06	 FLEXIBILITY:	EN 435 ASTM F137 < 20mm Pass
		 SLIP RESISTANCE:	EN 13893 DIN 51130 Class D5 R10
< 0.4 C.C.	IS: 3464/06	 ABRASION RESISTANCE:	EN 660-2 ASTM D3384 Wear Group P Pass
< 0.1 mm	IS: 3462/06	 RESIDUAL INDENTATION:	EN 433 ASTM F970 < 0.1 mm Static load 800 psi
		 CASTOR CHAIR:	EN 425 Continuous Use
> Blue Wool Standard 4	IS: 3462/06	 LIGHT FASTNESS/ COLOUR FASTNESS TO DAYLIGHT:	EN 20105: B02 > Blue Wool Standard 6
		 WEAR LAYER THICKNESS:	EN 429 1.0 mm
		 ELECTRICAL BEHAVIOR (body voltage):	EN 1815 < 2.0 kV
<0.4 %	IS: 3462/06	 DIMENSIONAL STABILITY:	EN 434 <0.4 mm
Good Resistance	IS: 3464/06	 STAIN and CHEMICAL RESISTANCE:	EN 423 Good Resistance
< 0.75 ^{1/8} m (Max.)	IS: 3462/06	CURLING:  SMOKE DENSITY:	ASTM E 662-05 < 450
> 1.05 kN/M	IS: 3462/06	 FUNGI and BACTERIA RESISTANCE:	Does not favor growth
No visible defect or exudation	IS: 3462/06	HEAT AGEING:  CLEAN ROOMS:	ASTM F51/50 Class A - non-shedding Suitable for use in following classes of clean room: ISO 14644-11999 Class 4
> 2 MJ/m ²	IS: 3462/06	ELASTIC PRODUCT:  MARINE USAGE: IMO RES A 053 (16) IMO MSC 0167 US Coast Guard Approved Marine Equipment Directive	Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2: (Surface Flammability / Heat Release)  1121
11 Shades	 COLOURS AVAILABLE:		11 Shades

For more details/clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.
 Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.
 The pattern given are with their product codes.