



Cushion
MATS

**PLAIN & DESIGN
CARPETS**



**WOODEN / VINYL
FLOORING**

**VENETIAN & VERTICAL
BLIND**



**WALL PAPER
&
FILM**



A. K. INTERNATIONAL

12/1, S. A. ALI AVE., KOL. - 17, PHONE : 2281-7518, 2280-9034/ 9830117275

Homogeneous Vinyl Flooring

Talitha®

The less you say, the more you can say with it. Earthy hues and minimalist textures complement almost any design scheme you can think of from the cool and contemporary to the warm and classic.



2349-751-4



2349-753-4



2349-757-4




2349-756-4



2349-758-4



2349-762-4



2349-755-4



2349-760-4



2349-761-4



2349-754-4

Key Features:

- Fully Flexible
- Heavy Duty
- Low Costs
- Durable & Tough
- Available in 1.5mm, 2.0mm & 3.0mm Sheet & Tiles
- Available in 1mm under Talitha Classic

Applications:

- Porta Cabins
- Budget Hotels / Retail
- Exhibition Centres
- Modular Offices
- Storage Areas etc.

TUSKER
VINYL FLOORING



UGC
Unglazed Ceramic



15 3402



PUR



R10

CE

11
Responsible for the CE mark

























Welding Rod No.
Talitha

- WR 2349-751-4
- WR 2349-753-4
- WR 2349-757-4
- WR 2349-756-4
- WR 2349-758-4
- WR 2349-762-4
- WR 2349-761-4
- WR 2349-755-4
- WR 2349-760-4
- WR 2349-754-4
- WR-Clear

RESPONSIVE Vinyl Flooring

The solution to every flooring need

Talitha®	Technical Data	Talitha®
<ul style="list-style-type: none"> Laminated Homogeneous Vinyl Flooring Polyurethane Reinforced 	 EN 685 : 1996  EN 649 : 1997 GENERAL PERFORMANCE: / TYPE OF FLOOR COVERING:	<ul style="list-style-type: none"> Heavy Duty Homogeneous Vinyl Flooring Polyurethane Reinforced
1.50 mm 2.00 mm	 THICKNESS: EN 428 IS: 3462/86	1.50 mm - 3.00 mm
1.5mm: 2m x 15m = 30m ² 2.0mm: 2m x 15m = 30m ²	 SHEET: EN 426 IS: 3462/86	2m x 15m = 30m ² 2m x 20m = 40m ²
30 x 30 cm 100 Tiles / box - 9 m ²	 TILES: EN 427 IS: 3462/86	300mm x 300mm 500mm x 500mm 610mm x 610mm
	 WEIGHT: EN 430 IS: 3464/86	1.5mm: 2.65 kg/m ² (Max.) 2.0mm: 3.20 kg/m ² (Max.) 3.0mm: 5.25 kg/m ² (Max.)
Does not support combustion	 REACTION TO FIRE: / FIRE RESISTANCE: EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 ASTM E848-06 IS: 3464/86	Class Bfl-S1 ≥ 8 kw/m ² Pass Type I
< 40 mm	 FLEXIBILITY: EN 435 ASTM F137 IS: 3462/86	< 20mm Pass
	 SLIP RESISTANCE: EN 13893 DIN 51130 IS: 3462/86	Class DS R10
< 0.4 C.C.	 ABRASION RESISTANCE: EN 660-2 ASTM D3384 IS: 3464/86	Wear Group P Pass
< 0.1 mm	 RESIDUAL INDENTATION: EN 433 ASTM F970 IS: 3462/86	< 0.1 mm Static load 800 psi
	 CASTOR CHAIR: EN 425 IS: 3462/86	Continuous Use
> Blue Wool Standard 4	 LIGHT FASTNESS:/ COLOUR FASTNESS TO DAYLIGHT: EN 20105: B02 IS: 3462/86	> Blue Wool Standard 6
	 WEAR LAYER THICKNESS: EN 429 IS: 3462/86	1.50mm - 3.00mm
	 ELECTRICAL BEHAVIOR (body voltage): EN 1815 IS: 3462/86	< 2.0 kV
<0.4 %	 DIMENSIONAL STABILITY: EN 434 IS: 3462/86	≤0.4%
Good Resistance	 STAIN and CHEMICAL RESISTANCE: EN 423 IS: 3464/86	Good Resistance
< 0.75 %m (Max.)	 CURLING: SMOKE DENSITY: ASTM E 662-05 IS: 3462/86	< 450
> 1.05 kN/M	 FUNGI and BACTERIA RESISTANCE: IS: 3462/86	Does not favor growth
No visible defect or exudation	 HEAT AGEING: CLEAN ROOMS: ASTM F51/68 IS: 3462/86	Class A - non-shedding Suitable for use in following classes of clean room : ISO 1465-11999 Class 4
> 2 MJ/m ²	 MARITIME USAGE: IMO RES A 653 (16) IMO MSC 61(87) US Coast Guard Approved Marine Equipment Directive IS: 3462/86	Annex 1 Part 2 (Smoke & Toxicity) Part 5 (Spread of Flame) and Annex 2 (Surface Flammability / Heat Release) 1121
10 Shades	 COLOURS AVAILABLE:	10 Shades Custom Colours Available

For more details/clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.
 Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance.
 The pattern given are with their product codes.