



*Cushion*  
**MATS**

**PLAIN & DESIGN  
CARPETS**



**WOODEN / VINYL  
FLOORING**

**VENETIAN & VERTICAL  
BLIND**



**WALL PAPER  
&  
FILM**



**A. K. INTERNATIONAL**

12/1, S. A. ALI AVE., KOL. - 17, PHONE : 2281-7518, 2280-9034/ 9830117275

# Homogeneous Vinyl Flooring

## Vega Plus®

Create the illusion of space where there isn't much to be had. Gentle, airbrushed textures on a palette of pastel shades help create an ambience that's light and airy, and at the same time, warm and soothing.



4699-571-4



4699-581-4



4699-582-4



4699-575-4



4699-576-4



4699-586-4



4699-574-4



4699-584-4



4699-594-4



4699-587-4

### Key Features:

















































- No Wax, No Polish
- Polyurethane Reinforced (PUR)
- Stain Resistant
- Hygienic
- Low Maintenance Costs
- Available in 1.50mm.

### Applications:

- Healthcare
- Offices / Commercial
- Labs / Clinics
- Hotels / Retail
- Heavy Industries etc.

# RESPONSIVE Vinyl Flooring

The solution to every flooring need

Vega Plus®	Technical Data	Vega Plus®
<ul style="list-style-type: none"> <li>Homogeneous Single Layered Vinyl Flooring</li> <li>Polyurethane Reinforced</li> </ul>	 <b>EN 645 : 1996</b> <b>EN 649 : 1997</b> GENERAL PERFORMANCE: /TYPE OF FLOOR COVERING: 	<ul style="list-style-type: none"> <li>Homogeneous Single Layered Vinyl Flooring</li> <li>Polyurethane Reinforced</li> </ul>
2.00 mm	 <b>IS: 3462/86</b> THICKNESS:  <b>EN 428</b>	2.00 mm 3.00 mm
2.00mm: 2m x 15m = 30m <sup>2</sup>	 <b>IS: 3462/86</b> SHEET:  <b>EN 426</b>	2.00mm: 2m x 15m = 30m <sup>2</sup> 3.00mm: 2m x 15m = 30m <sup>2</sup>
610mm x 610mm	 <b>IS: 3462/86</b> TILES:  <b>EN 427</b>	610mm x 610mm
-----	 <b>EN 430</b> WEIGHT: 	2.00mm: 3.50 kg/m <sup>2</sup> (Max.) 3.00mm: 5.25 kg/m <sup>2</sup> (Max.)
Does not support combustion	 <b>IS: 3464/86</b> REACTION TO FIRE: / FIRE RESISTANCE:  <b>EN 13501-1</b> <b>EN ISO 9239-1</b> <b>EN ISO 11925-2</b> <b>ASTM E648-06</b>	Class Bfl-S1 ≥ 6 kw/m <sup>2</sup> Pass Type I
< 40mm Pass	 <b>IS: 3462/86</b> FLEXIBILITY:  <b>EN 435</b> <b>ASTM F137</b>	< 20mm Pass
-----	 <b>EN 13893</b> SLIP RESISTANCE:  <b>DIN 51130</b>	Class DS R10
< 0.4 C.C	 <b>IS: 3464/86</b> ABRASION RESISTANCE:  <b>EN 660-2</b> <b>ASTM D3384</b>	Wear Group P Pass
< 0.1 mm	 <b>IS: 3462/86</b> RESIDUAL INDENTATION:  <b>EN 433</b> <b>ASTM F970</b>	< 0.1 mm Static load 800 psi
-----	 <b>EN 425</b> CASTOR CHAIR: 	Continuous Use
> Blue Wool Standard 4	 <b>IS: 3462/86</b> <b>IS: 9766/92</b> LIGHT FASTNESS/ COLOUR FASTNESS TO DAYLIGHT:  <b>EN 20105: 802</b>	> Blue Wool Standard 6
-----	 <b>EN 429</b> WEAR LAYER THICKNESS: 	2.0 mm, 3.0 mm
-----	 <b>EN 1815</b> ELECTRICAL BEHAVIOUR (body voltage): 	< 2.0 kV
< 0.4%	 <b>IS: 3462/86</b> DIMENSIONAL STABILITY:  <b>EN 434</b>	< 0.4 mm
Good Resistance	 <b>IS: 3464/86</b> STAIN AND CHEMICAL RESISTANCE:  <b>EN 423</b>	Good Resistance
-----	 <b>ISO 8302 (EN 12664)</b> THERMAL RESISTANCE: 	< 0.00809 m <sup>2</sup> /K/W
< 0.75 mm (Max.)	 <b>IS: 3462/86</b> CURLING:  <b>SMOKE DENSITY:</b>  <b>ASTM E 662-05</b>	< 450
No visible defect or exudation	 <b>IS: 3462/86</b> HEAT AGEING & EXUDATION:  <b>FUNGI and BACTERIA RESISTANCE:</b> 	Does not favor growth
> 2 MJ/m <sup>2</sup>	 <b>IS: 3462/86</b> ELASTIC PRODUCT:  <b>CLEAN ROOMS:</b>  <b>ASTM F51/68</b>	Class A - non-shedding Suitable for use in following classes of clean room - <b>ISO 1466-11999</b> Class 4
< 0.4%	 <b>IS: 3462/86</b> MOISTURE MOVEMENT:  <b>MARITIME USAGE:</b>  <b>IMO RES A 653 (18)</b> <b>IMO MSC 81(87)</b> <b>US Coast Guard Approved Marine Equipment Directive</b>	<b>Annex 1 Part 2</b> (Smoke & Toxicity) <b>Part 5</b> (Spread of Flame) and <b>Annex 2</b> (Surface Flammability / Heat Release)  <b>1121</b>
10 Shades	 <b>COLOURS AVAILABLE:</b>	10 Shades

For more details/ clarification regarding technical specifications, handling and installation, please contact Responsive Flooring.  
Note: The samples shown are representative. For technical reasons the material may vary in shades and appearance. The pattern given are with their product codes.